



A high-quality surveillance camera designed for outdoor use is the Eyemax AIR-C2032F-BW 2 Megapixel Outdoor Infrared Bullet IP Camera. This camera takes clear pictures with a resolution of 2 megapixels. It's great for checking on your house, business, or outside. This camera has 36 infrared LEDs that can light up to 60 feet (18.29 m)

You can cover a larger area with just one camera thanks to the Eyemax AIR-C2032F-BW's wide viewing angle. This is especially useful for large outdoor spaces, such as parking lots, warehouses, or yards. The lens also has an adjustable focus, ensuring that you can get the best possible view of your desired area.

## FEATURES

- 1/3" CMOS 2Megapixel 3.6 mm Fixed Lens
- 36 IR LEDs
- True Day and Night (ICR)
- 1080P Real-Time Image, High Resolution, True Color
- A-HD lossless video output
- Up to 1000 TVL resolution
- CMOS progressive scan, perfectly captures the moving object
- Support OSD menu
- Support motion alarm
- High speed, long distance, real-time transmission
- Auto color to Black and White at low illumination
- Support ICR switch, true day and night
- Support noise reduction function
- 20 ~ 30 m IR night view distance
- IP66 ingress protection

**SPECIFICATIONS**

<b>CAMERA</b>	
Image Sensor	1.3" CMOS
Resolution	1920 × 1080
Image System	PAL / NTSC
Min. Illumination	0 Lux (LED ON)
Lens	3.6mm Fixed Lens
IR Distance	20 ~ 30m
Water-Proof	IP66
Video Output	BNC × 1
Image Size	1080P (1920 × 1080)
Frame Rate	30 fps (60 Hz), 25 fps (50 Hz)
<b>FUNCTIONS</b>	
Screen Display	12 languages supported
Function Control	OSD
Day & Night	Yes (ICR)
BLC & HLC	Yes
Defog	Yes
WDR	Yes
3D DNR	Yes
Motion Detection	Up to 4 areas
Privacy Mask	Up to 8 areas
Defect Correction	Yes (support live and static defective pixel correction)
S/N Ratio	>52 dB (AGC off)
Electronic Shutter	1 / 50s ~ 1 / 50000s (PAL) 1 / 60s ~ 1 / 50000s (NTSC)
AGC	Yes
White Balance	ATW, AWC -> SET, Indoor, Outdoor, Manual
Advanced Image	Sharpness, saturation, brightness, etc. are adjustable
Mirror	Yes
Smart IR	Yes
<b>OTHERS</b>	
Power Supply	DC 12V (± 10%)
Working Environment	4 °F (-20 °C) ~ 122 °F (50 °C), 10% ~ 90% Humidity
Dimensions	Ø Ø 3.43 inch (8.71 cm) × 8.62 inch (21.89 cm)