



- 1/2.8" 2 Mega Pixel, EX-SDI Starlight 1080P High Definition
- 2.8-12mm Mega Pixel Lens
- IR Bullet • IR Cut Filter
- 4 white array leds, 50m-60m IR Distance
- Defog, HLI ,3DNR, SENSE UP
- Multi languages choice
- BLC, MIRROR, FLIP, ACE, PRIVACY, MONTION DETECT
- Digital-WDR (ON /15FPS; OFF / 30FPS)
- EX-SDI and CVBS Output, switch on HD-SDI and EX-SDI Output
- Support UCC

SPECIFICATIONS

| | |
|-----------------------|---|
| Image Sensor | 1/2.8" 2Mega Pixel Sensor |
| Effective Pixels | 2.0 Mega Pixels |
| Built-in Lens | 2.8 ~ 12mm 2Mega Pixel Lens |
| Signal System | PAL/NTSC |
| Horizontal Resolution | PAL:1920 × 1080P 25F/S NTSC:1920 × 1080P 30F/S |
| Sync. System | Internal Sync. |
| Sensor Area | 5.42mm × 3.41mm |
| Video Output | EX-SDI & CVBS Output, switch on HD-SDI & CVBS Output |
| S/N Ratio | More than 50dB (AGC OFF) |
| OSD Menu | Support |
| White Balance | Auto Tracking White Balance |
| Shutter Speed | 1/25 ~ 50,000Sec. |
| Leds | 4white array leds |
| Weather-proof | IP67 |
| Working Temperature | 14°F ~ 122°F(-10°C ~ 50°C) |
| Storage Temperature | -4°F ~ 140°F(-20°C ~ 60°C) |
| Power Requirement | DC12V, Max Power consumption Less Than 3W (When the infrared lamps turn on) |