

- EX-SDI 1080p
- IP68
- Outdoor
- DC 12V
- 1/2.9" Sony CMOS
- 2.8~12 mm Auto-Iris Varifocal Lens
- 80 IR LEDs
- True Day and Night(ICR)
- DNR (Digital Noise Reduction)
- AWB (Auto White Balance)
- SENS-UP
- EX-SDI or HD-SDI selectable
- Balun compatible
- NDAA
- Made in Korea



The Eyemax UIR-2182V-B camera has a 1/2.9" Sony CMOS sensor and can capture high-resolution 1080p video. It has a lens with a 2.8-12mm auto-iris that can be adjusted to any angle you want. This is useful when you want to focus on a specific area or see more of what's around you.

The camera can capture clear footage even in low light conditions. The camera's ability to capture sharp and clear images is further enhanced by the ICR function. This is especially useful for outdoor surveillance, where lighting conditions can vary greatly.

The Eyemax UIR-2182V-B EX-SDI1080pIP68 has an advanced technology, including DNR, AWB, and SENS-UP. These things work together to make sure the video is good, with less noise and clear colors.

Additionally, this camera is EX-SDI or HD-SDI selectable, offering you the flexibility to choose the type of signal output that best suits your needs. It is also Balun compatible, allowing for easy installation and integration with other security systems. Plus, it is NDAA compliant, meaning it is manufactured in Korea and adheres to strict quality standards.

Collsam Distribution is proud to be your trusted source for all Eyemax products, including the EX-SDI1080pIP68. As a leading distributor of security cameras and equipment, we are committed to providing customers with top-of-the-line products that offer unmatched performance and reliability. With the Eyemax EX-SDI1080pIP68, you can rest assured that your property is being monitored by a high-quality camera that will exceed your expectations.

**SPECIFICATIONS**

Resolution	1080P, 720P, 720P CROP
Sensor	1/2.9 inch SONY CMOS (IMX-222 / IM × 322)
Total Pixels	2000(H) × 1241(V) = 2,482,000
Effective Pixels	1944(H) × 1092(V) = 2,122,648
Scanning System	PROGRESSIVE
S/N (Y signal)	More than 52 dB (AGC Off)
Video Output	SMPTE274M (HD-SDI) / (CVBS: 1.0Vp-p (75ohm) : Option)
Min.Illumination	1 Lux at F1.2 / 0.1 Lux (B/W)
White Balance	AUTO / AUTO EXT / PRESET / MANUAL
shutter	AUTO / MANUAL (1/30sec ~ 1/60,000sec)
Brightness	ADJUSTABLE (0 ~ 20 STEP)
SENS_UP	OFF / × 2 / × 4 / × 8 / × 16 / × 32
DNR	OFF / LOW / MIDDLE / HIGH
BACKLIGHT	OFF / WDR / BLC / HLC
ACE	OFF / LOW / MIDDLE / HIGH
Day & Night	AUTO (Day <--> Night TIME Change) , COLOR , B/W, EXTERN,
Privacy	OFF / ON
Motion	OFF / SET
D.ZOOM	x1.0 ~ × 16.0
FLIP	OFF / ON
FREEZE	OFF / ON
Language	ENG, CHN, CHN(S), JPN, KOR
Sharpness	ADJUSTABLE (0 ~ 10 STEP)
DEFOG	OFF / SET
COMM	RS-485 (PELCO-D)
SMART IR (IR product SPEC.)	ADJUSTABLE (0 ~ 20 STEP)
Operating Temperature / Humidity	14°F ~ 122°F(-10°C ~ 50°C) / 30% ~ 80% RH
Storage Temperature / Humidity	-4°F ~ 140°F(-20°C ~ 60°C) / 20% ~ 90% RH
Power	DC12V [ AC24V / DC12V DualPower (option) ]
signal Transmission	The distant difference is occurred according to cable option and other circumstances. (based on 5C-HFBT : HD-SDI (200M) / EX-SDI (400M))