



- 1/2.9 inch SONY CMOS (IMX-291)
- High Definition (1080P)
- 0 Lux at IR On (IR LED 12 pcs)
- DNR (Digital Noise Reduction)
- WDR (Wide Dynamic Range)
- Day and Night (ICR Option)
- Easy Installation
- ICR Varifocal lens
- DC Auto IRIS Varifocal Lens
- DC Auto IRIS and TDN Varifocal Lens
- Focal Length : 7~22 mm

The Eyemax ULP-P2112V-W EX-SDI License Plate Capture camera is a great way to take clear pictures of license plates. This high-tech camera works well and accurately with advanced technology. It's great for watching over places like parking lots, toll booths, and other dangerous places.

This camera has a lens that can take clear pictures at a high quality. It can see license plate numbers from far away and has a size of 12.9 inches (32.77 cm). There are different types of surveillance using the 7-22 mm lens. You can adjust the focal length to fit your needs. You can choose from a wide-angle or a narrower focus with this camera.

But what truly sets the Eyemax ULP-P2112V-W apart from other license plate capture cameras is its innovative COB IR technology. With 12 COB (Chip on Board) IR illuminator, this camera can capture clear images even in low-light or no-light conditions. This makes it the ideal choice for 24/7 surveillance, providing you with reliable and accurate footage at all times.

SPECIFICATIONS

Resolution	1080P, 720P
Sensor	1/2.9 inch SONY CMOS (IMX-291)
Total Pixels	1945(H) x 1109(V) = 2.16M
Effective Pixels	1945(H) X 1097(V) = 2.13M
Scanning System	PROGRESSIVE
S/N (Y signal)	More than 52 dB (AGC Off)
Video Output	SMPTE292M (EX-SDI, HD-SDI) / (TVI, CVI, CVBS: 1.0Vp-p (75ohm) : Option)
Min.Illumination	0 Lux at IR On
White Balance	AUTO / AUTO EXT / PRESET / MANUAL
Electronic shutter speed	AUTO / MANUAL (1/30sec ~ 1/30,000sec) / FLICKER
SENS_UP	OFF / X2 ~ x32
DNR / ACE	OFF / LOW / MIDDLE / HIGH
BACKLIGHT	OFF / WDR / BLC / HLC
Day & Night	AUTO (Day <--> Night TIME Change) , COLOR , B/W, EXTERN
PRIVACY / FLIP / MOTION / DEFOG	OFF / ON
Language	ENG, CHN, CHN(S), JPN, KOR
Sharpness / Smart IR / Brightness	ADJUSTABLE (Sharpness : 0 ~ 10 STEP / Smart IR, Brightness : 0 ~ 20 STEP)
COMM.	RS-485(PELCO-D)
Temperature/Humidity	Operating (14°F ~ 120°F(-10°C ~ 50°C) / 30%~80% RH) / Storage (-20°C~+60°C / 20%~90% RH)
Power	DC12V
signal Transmission	The distant difference is occurred according to cable option and other circumstances. (based on 5C-HFBT : HD-SDI (200M) / EX-SDI (500M))

