

- 1/3" Sony Super HAD II CCD Low Ceiling Vandal-Resistant Infrared Camera
- External Adjustable 2.8 ~ 12 mm Varifocal Zoom Lens : IR Corrected
- 2.8~12 mm Wide to Telephoto angle Varifocal Lens
- Auto-Iris Built-in for Outdoor Monitoring
- External Adjustable Lens Focus and Zoom control
- 620 TV Line in Color
- 80ft (24.38 m) Infrared Range
- 35 IR LED
- Day and Night
- DC12V AC24V Dual Power (option)



## SPECIFICATIONS

|                                 |   |
|---------------------------------|---|
| MODEL                           | NTSC                                      |
| Resolution                      | 620 TV Line                               |
| Sensor                          | 1/3 INCH SONY SUPER HAD CCD II            |
| Total Pixels                    | 811(H) × 508(V) 410K pixels               |
| Effective Pixels                | 768(H) × 494(V) 380K pixels               |
| Scanning System                 | 2:1 Interlace                             |
| S/N (Y signal)                  | More than 50 dB (AGC Off)                 |
| Frequency                       | Horizontal: 15.734KHz / Vertical: 59.94Hz |
| Video Output                    | CVBS: 1.0Vp-p / 75ohm                     |
| Min.Illumination                | 0 Lux at IR On                            |
| White Balance                   | AWC                                       |
| Electronic shutter speed        | AUTO (1/60 sec ~ 1/100,000 sec)           |
| Day & Night                     | AUTO                                      |
| Operating Temperature/ Humidity | 14°F ~ 122°F(-10°C ~ 50°C) / 30% ~ 80% RH |
| Storage Temperature/ Humidity   | -4°F ~ 140°F(-20°C ~ 60°C) / 20% ~ 90% RH |
| Power                           | DC12V[AC24V / DC12V DualPower(option)]    |