

DoorBird Video Door Station D101, Polycarbonate housing, White Edition



- Polycarbonate housing, White Edition
- Stainless-steel button with illuminated LED ring
- 15 V DC (power 110 ~ 240 V AC) or Power over Ethernet (PoE 802.3af Mode-A)
- Power, electric door opener/strike, door chime, door opener button, network
- HDTV 720p, dynamic (VGA – HDTV) Camera
- High-end ultra-wide-angle hemispheric lens 180° horizontal, 90° vertical, straightened
- IR-capable Lens
- 802.11 b/g/n 2.4 GHz Wi-Fi
- Facilitates superior quality video
- Allows for a complete field of vision with the impressive camera angles
- Provides a powerful connection even in poor lighting scenarios
- Offers dependable Wi-Fi connection.



Technical data

General		Video	
Housing	Polycarbonate, UV-resistant Stainless-steel button with illuminated LED Ring	Camera	HDTV 720p, dynamic (VGA – HDTV)
Nameplate	Optional, can be engraved on the faceplate	Lens	High-end Ultra wide-angle Hemispheric Lens 180° horizontal, 90° vertical, straightened, IR-capable
Mounting type	Surface-mounted	Night-vision	Yes, Light sensor, Automatic IR-Cut Filter
Power supply	15VDC (power 110-240VAC) or Power over Ethernet (PoE 802.3af Mode-A)	Audio	
Weight	290g	Audio components	Speaker and microphone, Echo and Noise Canceller
Connectors	Power, Electric door opener / strike, Door chime, Door opener button, Network	Audio streaming	Two-way
Outdoor-ready	Yes, IP54	Network	
Approvals	CE, IC, FCC, IP54	WiFi	802.11b/g/n 2.4GHz
Dimensions	157 x 75 x 35mm (H x W x D)	Ethernet	Connector
Operating conditions	- 20 to +40°C Humidity 10 to 85% RH (non condensing)	Motion sensor	
Included accessories	Video Door Station, Mounting plate, Power supply unit (world-wide, 110 - 240V), DIN-Rail power supply sold separately, Screw package, Quickstart Guide	Type	Passive Infrared sensor (PIR)
EAN	4260423860001	Detection angle	180°
Current system requirements		Range	2-8m (dep. on environm.)
Mobile device	Latest iOS on iPhone /iPad, latest Android on Smartphone or Tablet	Illumination	
Internet	High-Speed landline broadband Internet connection, DSL, cable or Fiber, min. 500kbs Uploadbandwidth, no Socks- or Proxyserver	Lighting ring	12 intelligent Infrared LEDs
Network	802.11b/g/n 2.4GHz or Ethernet network, with DHCP	Range	2-8m (dep. on environm.)
Recommended installation height	Camera lens should be at a min. height of 125cm	Integrated wireless modules	
		WiFi	2,4 GHz, internal antenna
		RFID	433 MHz, internal antenna
		Bluetooth	Available separately
		Optional accessories	
		Sold separately	Faceplate F101, Faceplate F103, DIN-Rail Power supply A002, BirdGuard B101

Distributed By

Collsam Distributions; Inc.

Sales: (951) 282-8707 sales@Collsam.com

Support: (213) 210-5744 support@Collsam.com

Website: www.Collsam.com

