

DHI-ASR2102A

Access Reader



- PC material, acrylic panel and IP65, suitable for indoor and outdoor use
- Support contactless recognition of ID card
- Support card/fingerprint unlock
- · Support RS-485 communication protocol
- Support buzzer and indicator prompt
- Support anti-tampering alarm
- The built-in watchdog can detect and control the abnormal operation status of the equipment and perform recovery processing to ensure the long-term operation of the equipment
- All connection ports have overcurrent and overvoltage protection

Series Overview

As a key part of the access control system, the DHI-ASR2102A access control card reader supports card and fingerprint unlock, and sends the information to the access controller for verification. With a thin and elegant design, it is applicable to industrial zones, office buildings, schools, factories, stadiums, CBD, residential area, government properties, etc.

Tacketical	Specification

200.0	
Product 1	Γ
Buzzer	

Basic

Product Type	Fingerprint Card Reader
Buzzer	Yes
Casing	PC/acrylic panel
Function	
Unlock Mode	Card swiping/fingerprint Multiple unlocking modes
Card Type	ID card
Performance	

Ρ	er	101	m	ar	ıce

Response Time	0.1 s
Card Reading Distance	0 cm-5 cm (0"-1.97")
Fingerprint Sensor Type	Capacitive fingerprint sensor
Fingerprint Verification Mode	1:N
Fingerprint Recognition Time	1.5 s

Capacity

Fingerprint Capacity 3000

Port

1 channel RS-485









Alarm

Tamper Alarm	Yes	
--------------	-----	--

General

Power Supply	12V 0.5A DC
Protection	IP65 (silicon sealant is needed, see the manual)
Power Consumption	Standby ≤1.0W, working ≤1.7W
Product Dimensions	70 mm × 70 mm × 26 mm (2.76" × 2.76" × 1.02") (L × W × H)
Packaging Dimensions	110 mm × 97 mm × 90 mm (4.33" × 3.82"" × 3.54") (L × W × H, 1 in inner carton) 578 mm × 313 mm × 204 mm (22.76" × 12.32" × 8.03") (L × W × H, carton)
Operating Temperature	-20°C to +65°C (-4°F to +149°F)
Operating Humidity	5%RH–95% (non-condensing)
Operating Environment	Indoor; outdoor
Gross Weight	0.17 kg (0.37 lb)
Installation	Surface mount
Certifications	CF: FCC

