

DS-1006KI Keyboard with Joystick



- 128 x 64 Screen
- 4-Axis Joystick
- PTZ Control and Picture Capture via Joystick
- Manage 1 Admin and 15 Operators
- System Upgrade/Import/Export Configuration Files via USB Flash Disk

Connects to the Multi-functional Video Center (MVC) and Matrix Access Gateway (MAG) via the RS-422 serial port. Connects to a DVR via the RS-485 serial port, with front panel button operation possible.

Dome camera connection is via the RS-485 serial port.

Available model:
DS-1006KI

Specifications

DS-1006KI	
System	
LCD Screen	128 x 64 pixel screen
Joystick	4-axis joystick
Control Mode	RS-232, RS-422, RS-485
External Interfaces	
Serial Interface	1 RS-232, 1 RS-422, 1 RS-485
USB Interface	1 x USB 2.0 for firmware upgrade and configuration file import/export
General	
Power Supply	12 VDC
Consumption	≤4.5 W
Working Temperature	14° to 131° F (-10° to 55° C)
Working Humidity	10% to 90% (non-condensing)
Dimensions (W x D x H)	17.1" x 7.6" x 4.3" (435 mm x 193 mm x 110 mm)
Weight	≤2.2 lb (1 kg)

Distributed By

Collsam Distributions; Inc.
Sales: (951) 282-8707 sales@Collsam.com
Support: (213) 210-5744 support@Collsam.com
Website: www.Collsam.com

