

SPC-2001 USB Joystick Controller



Key features

- Superior system control of PTZ cameras with Wisenet WAVE VMS, Wisenet Viewer CMS, or NVR/DVR
- USB-A Interface
- Requires Computer that Supports Direct X
- 12 Buttons and 3-Axis Joystick
- 3D joystick control
- Quick and easy installation with USB connection

Joystick		
Axis		Hall-effect 3 Axis
Button		12ea
Performance		
Range of Movement	X/Y-Axis	±28°
	Z Axis	±23.5°
Center		Two Spring, Two Directions
Minimum Power		0.109 [N·m]
Operating Power		0.151 [N·m]
Maximum Power		0.169 [N·m]
Materials		
Housing		ABS
Handle		Poly Carbonate
Cover		Rubber (Button)
Shaft		SUM24L + Ni plating
Interface		
Port		4-pin USB Type A
Software		
Drivers		Standard DirectX Drivers (DirectInput)
Electric Features		
Operating Voltage		(DC 5 [V]), Vdd = 5 [V] (±0.5 [V]) via USB
Operating Current		50 [mA]
Operating Environment		
Temperature		0°C to +40°C (20% ~ 85% RH)
Materials		
Cable Length		2 [m]
Size(WxDxH)		182 X 182 X 106 [mm]
Weight		405g
Color		Black