



Compatible with HD-TVI / HD-CVI / A-HD / 960H / Analog Cameras • No Power Required • Push-in Terminal Block • Transmission Signal: 1080P, Max.250M 7200P, Max.300M • Built-in Surge & Transmission Protection • Super Interference Rejection

SPECIFICATIONS

PROPERTIES

HD-TVI / HD-CVI / A-HD / 960H / Analog Hybrid Balun

Transmission Signal	1 Channel
Transmission Distance	720P: 250m (max) 1080P: 200m (max)
Category Type	UTP CAT5/5E/6
VIDEO TRANSMISSION PROPERTIES & PORT	
Coaxial Video Connector	BNC-M
Twisted-Pair Video Connector	Push-Terminal
Compatible Format	HDTV, HDCVI, AHD, 960H, 720P
Resolution	720p/1080p
Anti-Interference	>60db
PROTECTION	
ESD	1a contact discharge electricity level 3 1b air discharge electricity level 3 Per: IEC61000 ~ 4-2
Coaxial cable connector	2KV(common-code) Per: IEC1000 ~ 4-5
UTP Cable Connector	2KV(different-code), 4KV(common-code), Per: IEC1000 ~ 4-5
IMPEDANCE	
BNC Male	75 ohms
UTP Cable	100 ohms
PHYSICAL PROPERTIES	
Shell	ABS
Color	Black
N.W.	25g
STABILITY	
MTBF	>10000H
ENVIRONMENTAL	
Operating Temperature	-10 ~ 55°C
Storage Temperature	-20 ~ 75°C
Humidity	0 ~ 95% (non-condensing)