

540TVL Bullet Camera with Fixed Lens



1/3" Sony Super HAD CCD • 3.6mm Fixed Lens • Day & Night • Weather-Resistant • ATW (Auto Trace White Balance) • BLC (Back Light Compensation) • ESC (Electronic Shutter Control)

Overview

The BU 5005E is one of top quality and affordable cameras. The BU 5005E has a small joystick OSD control on closure to make easy access setting up the camera and crystal clear high resolution of 560 TV lines at an impressive 0.03 lux rating with help from its Day & Night function.

FEATURES

- 1/3" Sony Super HAD CCD
- 560 (H) TV Line (Color) / 580 (H) TV Line (B/W)
- 3.6mm Fixed Lens

540TVL Bullet Camera with Fixed Lens

- External OSD (On Screen Display) Control
- Day & Night
- 0.1 Lux (B/W)
- DC 12V

SPECIFICATIONS

Image Pick-Up Device	1/3" SONY SUPER HAD CCD
TV System	NTSC
Effective Pixels	768(H) × 494(V)
Scanning Frequency	15.734KHz(H) / 59.94Hz(V)
Scanning System	525 Line (2:1 Interlace)
Synchronization	Internal
Resolution	540TV Lines
Minimum Illumination	0.1 Lux
S/N Ratio	More than 50dB
White Balance	ATW / AWB / FIXED / MANUAL
Gamma Characteristic	r=0.45 Selectable
Video Output	CVBS: 1.0Vp~p, 75Ω
Electronic Shutter Speed	Auto / Manual (1/60Sec ~ 1/100,000Sec)
OSD	Built-in
BLC	ON / OFF
AGC	ON / OFF
Day & Night (Color / BW)	Color / Auto / BW
Display Adjust	Contrast / Sharpness / CB-Gain / CR-Gain
Privacy	ON / OFF (4 Programmable Zone)
Power Supply	DC 12V
Power Consumption	120mA
Lens	3.6mm Fixed Board Lens
Operational Temperature	14°F ~ 122°F(-10°C ~ 50°C) RH 95% Max.
Storage Temperature	-4°F ~ 140°F(-20°C ~ 60°C) RH 95% Max.

540TVL Bullet Camera with Fixed Lens

Dimension	21mm(W) × 21mm(H) × 69mm(D)
Weight	60g