



- 1/3 inch SONY SUPER HAD CCD II
- High Resolution (620 TVL)
- High Sensitivity
- Weather Proof Housing
- 0 Lux at IR On (IR LED 35 pcs)
- Lens Option : Manual Varifocal Lens : 2.8^-12mm
- Varifocal Lens 2.8-1 2mm
- External Zoom and Focus Control
- Day and Night Function
- Easy Installation

SPECIFICATIONS	NTSC: NTSC PAL: PAL
Resolution	620 TV Line
Sensor	1/3 INCH SONY SUPER HAD CCD II
Ictal Pixels	NTSC: 811(H) × 508(V) 410K pixels PAL: 795(H) × 595(V) 470K pixels
Effective Pixels	NTSC: 768(H) × 494(V) 380K pixels PAL: 752(H) × 582(V) 440K pixels
Scanning System	2:1 Interlace
S/N (Y signal)	More than 50 dB (AGC Off)
Frequency	NTSC: Horizontal: 15.734KHz / Vertical: 59.94Hz PAL: Horizontal: 15.625KHz / Vertical: 50.00Hz
Video Output	CVBS: 1.0Vp—p / 75ohm
Minillumination	0 Lux at IR On
White Balance	ATW
Electronic shutter speed	NTSC: AUTO (1/60sec — 1/100,000sec) PAL: AUTO (1/50sec ~ - 1/100,000sec)
Day & Night	AUTO
Operating Temperature/ Humidity	14°F ~ 122°F(-10°C ~ 50°C) / 30% — 80% RH
Storage Temperature/ Humidity	-4°F ~ 140°F(-20°C ~ 60°C) / 20% — 90% RH
Power	DC12V [AC24V / DC12V DualPower (option)]