


Remotely monitor a UPS system

A UPS monitoring card, the CyberPower RCCARD100 monitors the operation of select CyberPower UPS that are setup with PowerPanel® Cloud system.

A secure web portal or mobile application is used to remotely monitor a UPS and provide notifications on power events.

The RCCARD100 is a hot swappable plug-and-play design, allowing fast installation, or replacement without interrupting the operation of the UPS. A RJ-45 Ethernet connection is used to connect the card to a network and PowerPanel® Cloud. The card supports user-upgradeable firmware to keep functionality up to date. The RCCARD100 comes with a three-year warranty.



FEATURES

- Real-time monitoring: Yes
- Cloud Monitoring: Yes
- Plug and Play Installation: QR Code for quick installation
- Auto Event Notifications: Yes
- Remote Monitoring: Mobile App and Web-based App
- User Upgradeable Firmware: Yes
- RoHS Compliant: Yes
- Warranty: 3 year

SPECIFICATIONS

GENERAL

Data Link Protocol	Ethernet 100Base-TX, Ethernet 10Base-T
Network Protection RJ45	Ethernet RJ45
LED Indicators	Tx/Rx, LINK
Color	Black

PHYSICAL DIMENSIONS

Physical Dimensions - WxHxD (cm)	5.41 x 3.61 x 7.62 cm
Physical Dimensions - WxHxD (mm)	54 x 36 x 76 mm
Physical Dimensions - WxHxD (in)	2.13 x 1.42 x 3 in
Weight (kg)	0.03
Weight (lb)	0.07

SHIPPING DIMENSIONS

Shipping Dimensions - WxHxD (cm)	5.84 x 16.51 x 16.76 cm
Shipping Dimensions - WxHxD (mm)	58.42 x 165.1 x 167.64 mm
Shipping Dimensions - WxHxD (in)	2.3 x 6.5 x 6.6 in
Weight (kg)	0.15
Weight (lb)	0.32

ENVIRONMENTAL

Operating Elevation	0 - 10,000 ft (0 - 3,048 m)
Operating Relative Humidity	0 - 90 % (non-condensing)
Operating Temperature	32 - 104°F (0 - 40°C)
Storage Elevation	0 - 50,000 ft (0 - 15,239 m)
Storage Relative Humidity	0 - 95% (non-condensing)
Storage Temperature	14 - 122°F (-10 - 50°C)

CERTIFICATIONS

Environmental	RoHS Compliant
Safety	FCC DoC Class B CE

WARRANTY

Extended Warranty Option	WEXT5YR-ACC1A
Product Warranty	3 Year Limited Warranty