

12 VDC, 1 A Power Adapter



- Supports 100 VAC to 240 VAC Wide-range Voltage Input
- Meets the Demands of Voltage Fluctuation
- Accurate Over-current and Over-voltage Protection



Technical Specification

Electrical

Input	100 VAC to 240 VAC, 50/60 Hz
Output	12 VDC, 1 A

Protection

Protections	Surge Over-current Voltage Load
ESD	IEC61000-4-2 ±4 kV Contact; ±8 kV Air

Environmental

Operating Temperature	-10° C to +55° F (14° F to 131° F)
Operating Humidity	< 90%, Relative

Physical Properties

Dimensions (L x W x H)	60.80 mm x 37.80 mm x 33.50 mm (2.39 in. x 1.49 in. x 1.32 in.)
Installation Mode	Pluggable Installation
Color	Black
Input Plug	2-pin North American Plug
Outgoing Cord	24 AWG, 1500.0 mm (59.06 in.)
DC Plug	ø5.50 mm x ø2.10 mm x 10.0 mm (ø0.22 in. x ø0.08 in. x 0.39 in.)

Certifications

Safety	UL
--------	----

Distributed By

Collsam Distributions; Inc.

Sales: (951) 282-8707 sales@Collsam.com

Support: (213) 210-5744 support@Collsam.com

Website: www.Collsam.com

