

# Telpix TVST-TR2908A DVRs. Connect Analog, AHD, And IP Cameras Simultaneously For 8 Channel Recording And Playback



## FEATURES

- Quadbrid DVR ( TVI / AHD / IP / 960H & Analog camera support ) 8 CH video input, 1080P / 720P / D1 recording
- 1 CH IPC 1080P/960P/720P/WD1/D1 recording. CVBS (analog) out (can be used as spot out)
- HDMI 1080P output, true high resolution display
- Adopt high profile compression format to get high-quality video at much lower bit rate
- Multi-mode recording: manual / timer / motion
- Playback: 8 CH simultaneously playback
- Search: time / calendar, events ( motion )
- Express and flexible backup via USB, network
- Pentaplex : preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE Network protocol, IE browse and CMS supported
- Remote control via IE or CMS: preview, playback, backup, PTZ and configuration
- Dual stream technology to encode recording stream and network stream respectively. User can adjust

## network stream to fit bandwidth without changing recording quality

- Intuitive and user-friendly Graphic User Interface ( GUI ), Windows style operation by mouse Multi-user on line simultaneously
- Authorization management, log review and device status review
- Support PTZ preset and auto cruise, up to 128 presets and 8 cruises
- Powerful smart phone surveillance supporting iPhone, Andriod
- Support NAT function, support QR code scanning by mobile phone

# Telpix TVST-TR2908A DVRs. Connect Analog, AHD, And IP Cameras Simultaneously For 8 Channel Recording And Playback

## SPECIFICATIONS

Video Input / Resolution	8 CH (BNC) / 1080P
IP Cam Input	IPC × 1/6MPS
Output	VGA × 1: 1080P HDMI × 1:1080P BNC × 1: 1080P(CVBS or SPOT)
Multi Operation	Pentaplex: Live Display / Record / Playback / Backup / Remote Access
OS	Embedded Linux
Recording	720P (1280 × 720) , 1080P Lite(960 × 1080), 1080P (1920 × 1080)
Recording (720P)	200fps: 25fps per channel
Recording (1080P Lite)	200fps: 25fps per channel
Recording (1080P)	100fps: 12fps per channel
Audio in	RCA × 4
Two-Way Audio	Yes
Mic in	No
Audio out	RCA × 1
Bit Rate	768Kbps ~ 8Mbps
Encode	VBR / CBR
Quality Levels	6 level
Recording Modes	Manual, Timer, Motion, Sensor
File Management	Lock, Unlock, Reserving time, Redundancy
Local Playback	8 CH
Search	Time, Motion,Sensor,Single or Multi-channel
Function	Play, Pause, FF,FB,Shutter Control ,Jog,Digital zoom
Alarm Modes	Sensor,Motion,Video loss
Alarm Triggering	Record, PTZ move, Relay out,E-mail, etc
Network Interface	RJ45 × 1
Remote Playback	4CH
Master Steam	4CH
Dual-stream	Individual Network Video Stream and local recording stream, set seperately

# Telpix TVST-TR2908A DVRs. Connect Analog, AHD, And IP Cameras Simultaneously For 8 Channel Recording And Playback

PTZ Protocol	Pelco D, Pelco P, RANGE, VISCA, DSCP, VIDO, STAR, NEON, MINKING, LILIN
Protocal	TCP/IP, UDP, DHCP, DNS, PPPOE, DDNS, SMTP, NAT, HTTP
Remote Viewing	CMS / Web Browser / Mobile (iOS/Android)
Remote Users	10 users online, dual stream
SATA HDD	Up to 6TB (1 × 6TB)
Alarm in	4
Alarm out	1
RS485	RS485 × 1 (for PTZ or Keyboard)
USB	USB2.0 × 2 (for mouse and USB backup device)
Accessory	Remote controller, SATA cable, USB mouse
Power Supply	DC: 12V
Working Environment	-10°C ~ 50°C (14°F ~ 122°F) , 10% ~ 90%(Humidity)
Dimension	255(W)mm × 210mm(D) × 42(H)mm 10(W)in×8.27(D)in×1.65(H)in