

HD-TVI 1080p (2MP) Outdoor IR Bullet Camera with 25 IR LED, IP68, Fixed Lens, DC 12V



1/2.9 inch SONY CMOS (IMX-222)/ Resolution (1080P) • TVI (Transport Video Interface)/ 0 Lux at IR On (04 pcs)/ Upgraded Waterproof Housing (IP68rating) • Smart IR (option)/ DNR (Digital Noise Reduction) • Day & Night (ICR Option) • Easy Installation • Fixed Lens 4mm

SPECIFICATIONS

| | |
|------------|-------|
| RESOLUTION | 1080P |
|------------|-------|

HD-TVI 1080p (2MP) Outdoor IR Bullet Camera with 25 IR LED, IP68, Fixed Lens, DC 12V

| | |
|----------------------------------|--|
| SENSOR | 1/2.9 inch SONY CMOS (IMX-222) |
| TOTAL PIXELS | 2000(H) × 1241(V) = 2,482,000 |
| EFFECTIVE PIXELS | 1944(H) × 1092(V) = 2,122,648 |
| SCANNING SYSTEM | PROGRESSIVE |
| S/N (Y SIGNAL) | More than 52 dB (AGC Off) |
| VIDEO OUTPUT | TVI / (CVBS: 1.0Vp-p (75ohm) : Option) |
| MIN.ILLUMINATION | 0 Lux at IR On |
| WHITE BALANCE | AUTO |
| SHUTTER | AUTO / MANUAL (1/30sec ~ 1/60,000sec) |
| AGC | ON |
| DNR | ON |
| DAY & NIGHT | ON |
| OPERATING TEMPERATURE / HUMIDITY | 14°F ~ 122°F(-10°C ~ 50°C) / 30% ~ 80% RH |
| STORAGE TEMPERATURE / HUMIDITY | --4°F ~ 140°F(-20°C ~ 60°C) / 20% ~ 90% RH |
| POWER | DC12V |
| SIGNAL TRANSMISSION | The distant difference is occurred according to cable option and other circumstances. (coaxial cable 300M) |