

Eyemax / EX-SDI 1080P Outdoor Bullet Camera with 3.6mm Fixed Lens, DC 12V



1/2.9 inch SONY CMOS (IMX-222 or imx-322) / HD-SDI (1080P, 720P) • 1 Lux at F1.2 / 0.1 Lux (B/W) / WDR (Wide Dynamic Range) • DNR (Digital Noise Reduction) / Day & Night / Easy Installation • Fixed Lens

SPECIFICATIONS

Resolution	1080P, 720P
Sensor	1/2.9 inch SONY CMOS (IMX-222 or IMX-322)

Eyemax / EX-SDI 1080P Outdoor Bullet Camera with 3.6mm Fixed Lens, DC 12V

Total Pixels	2000(H) × 1241(V) = 2,482,000
Effective Pixels	1944(H) × 1092(V) = 2,122,648
Scanning System	PROGRESSIVE
S/N (Y signal)	More than 52 dB (AGC Off)
Video Output	SMPTE292M (HD-SDI) / (CVBS: 1.0Vp-p (75ohm) : Option)
Min.Illumination	1 Lux at F1.2 / 0.1 Lux (B/W)
White Balance	AUTO / AUTO EXT / PRESET / MANUAL
Electronic shutter speed	AUTO / MANUAL (1/30sec ~ 1/30,000sec) / FLICKER
SENS_UP	OFF / × 2 ~ × 32
DNR / ACE	OFF / LOW / MIDDLE / HIGH
BACKLIGHT	OFF / WDR / BLC / HLC
Day & Night	AUTO (Day <--> Night TIME Change) , COLOR , B/W, EXTERN
PRIVACY / FLIP / FREEZE	OFF / ON
MOTION / DEFOG	OFF / SET
Language	ENG, CHN, CHN(S), JPN, KOR
Sharpness	ADJUSTABLE (0 ~ 10 STEP)
Brightness	ADJUSTABLE (0 ~ 20 STEP)
COMM.	RS-485(PELCO-D)
Temperature/Humidity	Operating (−10°C ~ +50°C / 30% ~ 80% RH) / Storage (−20°C ~ +60°C / 20% ~ 90% RH)
Power	DC12V
signal Transmission	The distant difference is occurred according to cable option and other circumstances. (based on 5C-HFBT : HD-SDI 200M / EX-SDI 500M)