



- 1/2.8" 2 Mega Pixel, EX-SDI Starlight 1080P High Definition
- 2.8-12mm Mega Pixel Lens
- IR Bullet
- IR Cut Filter
- 3 white array LED, 131~164ft (40~50m) IR Distance
- Defog, HLI ,3DNR, SENSE UP
- Multi languages choice
- BLC, MIRROR, FLIP, ACE, PRIVACY, MONTION DETECT
- Digital WDR (ON /15FPS; OFF / 30FPS)
- EX-SDI & CVBS Output, switch on HD-SDI and EX-SDI Output
- Support UCC

## SPECIFICATIONS

Image Sensor	1/2.8" 2Mega Pixel Sensor
Effective Pixels	2.0 Mega Pixels
Built-in Lens	2.8 ~ 12mm 2Mega Pixel Lens
Signal System	PAL/NTSC
Horizontal Resolution	PAL:1920 × 1080P 25F/S NTSC:1920 × 1080P 30F/S
Sync. System	Internal Sync.
Sensor Area	5.42mm × 3.41mm
Video Output	EX-SDI & CVBS Output, switch on HD-SDI & CVBS Output
S/N Ratio	More than 50dB (AGC OFF)
OSD Menu	Support
White Balance	Auto Tracking White Balance
Shutter Speed	1/25 ~ 50,000Sec.
Leds	2white array leds
Weather-proof	IP67
Working Temperature	14°F ~ 122°F(-10°C ~ 50°C)
Storage Temperature	-4°F ~ 140°F(-20°C ~ 60C)
Power Requirement	DC12V, Max Power consumption Less Than 3W (When the infrared lamps turn on)