

# UIR-1712V EX-SDI Outdoor Bullet, 2MP(1080p), IP66, 72 IR, 2.8~12mm Lens, Defog , 3D-DNR, ICR, DC 12V

- 1/2.8" 2 Megapixel panasonic Sensor
- EX-SDI 1080P High Definition
- 2.8-12mm Mega Pixel Lens
- IR Bullet
- IR Cut Filter
- 72pcs IR Leds
- Defog
- HLI
- 3 DNR
- SENSE UP
- Multi languages choice
- BLC
- MIRROR
- FLIP
- ACE
- PRIVACY
- MONTION DETECT
- WDR(ON /15FPS; OFF
- 30FPS)
- EX-SDI and CVBS Output
- Switch on HD-SDI and CVBS Output



## SPECIFICATIONS

Image Sensor:	1/2.8" 2Mega Pixel Sensor
Effective Pixels:	2.0 Mega Pixels
Built-in Lens:	2.8 ~ 12mm Mega Pixel Lens
Signal System:	PAL/NTSC
Horizontal Resolution	PAL:1920 × 1080P 25F/S NTSC:1920 × 1080P 30F/S
Sync. System:	Internal Sync.
Sensor Area:	5.42mm × 3.41mm
Video Output:	EX-SDI and CVBS Output, switch on HD-SDI and CVBS Output
S/N Ratio:	More than 50dB (AGC OFF)
OSD Menu	Support
White Balance:	Auto Tracking White Balance
Shutter Speed:	1/25 ~ 50,000Sec.
IR Leds:	72pcs
Working Temperature:	14°F ~ 122°F(-10°C ~ 50°C)
Storage Temperature:	-4°F ~ 140°F(-20°C ~ 60°C)
Power Requirement:	DC12V, Max Power consumption Less Than 3W (When the infrared lamps turn on)
Weight:	1.25kg