

High Performance Eyemax UIR-2342V-B X-SDI 1080p IR Bullet Camera with 8 COB IR and 2.8~12mm Lens



FEATURES


- 2.8 ~ 12mm Auto-Iris Varifocal Lens
- 1/2.9" Sony CMOS
- 0 Lux at IR On (8 pcs of COB IR LED)
- Upgraded Waterproof Housing (IP68 Rating)
- Smart IR / DNR (Digital Noise Reduction) / True Day and Night
- (ICR) RS-485 Option
- Easy Installation
- DC 12V

Introducing the Eyemax UIR-2342V-B X-SDI Bullet Camera, the ultimate surveillance solution for your security needs. This high-definition camera boasts a 2MP image sensor and 1080p resolution, delivering crystal-clear footage with exceptional detail and clarity. This camera can perform well even in low-light conditions, giving you round-the-clock protection.

The Eyemax UIR-2342V-B X-SDI Bullet Camera is excellent and has advanced technology. It can be used both inside and outside. With its IP68 ingress protection, this camera is completely waterproof, dust proof, and built to withstand harsh weather conditions. This camera will still work well if it rains, snows, or the weather is freezing.

High Performance Eyemax UIR-2342V-B X-SDI 1080p IR Bullet Camera with 8 COB IR and 2.8~12mm Lens

SPECIFICATIONS

Resolution	1080p, 720p, 720p CROP
Sensor	1/2.9 inch SONY CMOS (IMX-222 / IM x 322)
Total Pixels	2000(H) x 1241(V) = 2,482,000
Effective Pixels	1944(H) x 1092(V) = 2,122,648
Scanning System	Progressive
S/N (Y Signal)	More then 52 dB (AGC Off)
Video Output	SMPTE274M (HD-SDI) / CVBS: 1.0Vp-p (75ohm)
Min. Illumination	IR Product: 0 Lux at IR On
White Balance	Auto / Auto Ext / Preset / Manual
Shutter	Auto / Manual (1/30sec ~ 1/60,000sec)
Brightness	Adjustable (0 ~ 20 Step)
Sens Up	OFF / x 2 / x 4 / x 8 / x 16 / x 32
DNR	OFF / Low / Middle / High
Backlight	OFF / WDR / BLC / HLM
ACE	OFF / Low / Middle / High
Day & Night	Auto (Day <--> Night Time Change), Color, B/W, Extern
Privacy	OFF / ON
Motion	OFF / SET
Digital Zoom	x1 ~ x 16
Flip	OFF / ON
Freeze	OFF / ON
Language	English, Chinese, Chinese(S), Japanese, Korean
Sharpness	Adjustable (0 ~ 10 Step)
Defog	OFF / SET
Communication Port	RS-485 (Pelco-D)
Smart IR	Adjustable (0 ~ 20 Step)
Operating Temp / Humidity	-10°C ~ +50°C(14°F ~ 122°F) / 30% ~ 80% RH
Storage Temp / Humidity	-20°C ~ +60°C(-4°F ~ 140°F) / 20% ~ 90% RH
Power	DC 12V 
Signal Transmission	The distant difference is occurred according to cable option and other circumstances. (based on 5C-HFBT : HD-SDI (200M) / EX-SDI (400M))