



SPECIFICATIONS

Resolution	HD-SDI(1080P, 720P) / 1000 TV LINE OVER
Sensor	1/ 3 INCH SONY CMOS
Total Pixels	2010(H) × 1108(V) = 2,227,080
Effective Pixels	1944(H) × 1092(V) = 2,122,648
Scanning System	PROGRESSIVE
S/ N (Y signal)	More than 52 dB (AGC Off)
Video Output	SMPTE292M (HD-SDI) / CVBS: 1.0Vp-p (75ohm)
Min.Illumination	0 Lux at IR On
White Balance	AUTO / AUTO EXT / PUSHING / MANUAL
Electronic shutter speed	AUTO / Manual (1/ 30sec ~ 1/ 60,000sec)
Brightness	ADJUSTABLE (0 ~ 20 STEP)
SENS_UP	OFF / × 2 / × 3 / × 4
DNR	OFF / LOW / MIDDLE / HI
WDR/ BLC	OFF / WDR / BLC
HLM	OFF / SET
ACE	OFF / ON

Day & Night	AUTO (Day <--> Night TIME Change) , COLOR , B/ W, EXTERN, MDIR
Smart IR	OFF / ON
Privacy	OFF / ON (31 Zone)
Motion Detection	OFF / ON
D.ZOOM	0 ~ × 127
FLIP	OFF / ON
FREEZE	OFF / ON
Image Conversion	OFF / ON
Language	ENGLISH
Sharpness	ADJUSTABLE (0 ~ 10 STEP)
COMM.	RS-485(PELCO-D)
Operating Temperature/ Humidity	14 °F (-10 °C) ~ 122 °F (50 °C) / 30% ~ 80% RH
Storage Temperature/Humidity	-4 °F (-20 °C) ~ 140 °F (60 °C) / 20% ~ 90% RH
Power	DC12V Only
Signal	328.08 ft (100 m) ~ 492.13 ft (150 m) Max transmission range is depends on the cable manufacturer and the installation environment.)

Dimensions

