

SUPERDOME Camera

- ▶ HD-SDI FULL HD (1080p) Security Camera
- ▶ 2.8~12mm Mega-Pixel AVF Lens
- ▶ DC 12V or AC 24V



XDL 204V-B



Available in White

XDL 204V-W

HD-SDI : 1080P SUPERDOME® CAMERA WITH ICR & DUAL POWER

- 3-Axis Construction :
By adjusting '3-Axis' control, you get a straight view regardless whether camera is installed on a wall or ceiling
- 1080p / 720p Resolution
- 1/3 inch SONY 2 Mega-Pixel CMOS
- Minimum Illumination - 1.0 Lux at F1.2
- OSD (On Screen Display) - Easy Camera Setup
- 3DDNR (3D Digital Noise Reduction) - Clear Motion Noise
- HD-SDI Output / Standard CCTV Output Available Both in One Camera
- 2.8~12mm DC Auto IRIS Vari-Focal Lens (External Angle & Focus Control)
- DC 12V / AC 24V : DUAL POWER

2 MEGA PIXEL
Up To 1080p

HIGH DEFINITION OVER COAX

USE YOUR EXISTING COAX CABLE

HDSDI

| XDL 204V | |
|----------------------------------|-----------------------------------------------------------------------------------------------|
| Resolution | HD-SDI(1080P, 720P) / 1000 TV Line Over |
| Sensor | 1/3" SONY CMOS |
| Total Pixels | 2010(H) X 1108(V) = 2,227,080 |
| Effective Pixels | 1944(H) X 1092(V) = 2,122,648 |
| Scanning System | Progressive Scan |
| S/N (Y Signal) | More than 52 dB(AGC Off) |
| Video Output | SMPT292M (HD-SDI) / CVBS : 1.0Vp-p (75ohm) |
| Min. Illumination | 1 Lux at F1.2 / 0.1 Lux (B/W) |
| White Balance | AUTO / AUTO EXT / PUSHING / MANUAL |
| Electronic Shutter Speed | AUTO / MANUAL(1/30sec ~ 1/30,000sec) |
| Brightness | Adjustable (0~20 Step) |
| Sens up | OFF / X2 / X3 / X4 |
| DNR | OFF / LOW / MIDDLE / HI |
| WDR / BLC | OFF / WDR / BLC |
| HLM | OFF / SET |
| ACE | OFF / ON |
| Day & Night | AUTO (Day <-> Night TIME Change), COLOR, B/W |
| Privacy | OFF / ON (28 Zone) |
| Motion Detection | OFF / ON |
| D. Zoom | 0 ~ X112 |
| FLIP | OFF / ON |
| FREEZE | OFF / ON |
| Language | ENGLISH |
| Sharpness | ADJUSTABLE (0~10 STEP) |
| Mirror | ON / OFF |
| COMM. | RS-485(PELCO-D) |
| Operating Temperature / Humidity | -10°C~+50°C (14°F ~ 122°F) / 30% ~ 80% RH |
| Storage Temperature / Humidity | -20°C~+60°C (-4°F ~ 140°F) / 20% ~ 90% RH |
| Power | DC 12V / AC 24V |
| HD-SDI | 100~150m |
| Transmission Range | Max transmission range is depends on the cable manufacturer and the installation environment. |

X22 MORE COVERAGE than Conventional CCTV Camera

