



FULL HD OVER COAX USE YOUR EXISTING COAX CABLE

HDSDI



HD-SDI FULL HD (1080p) Security Camera

2.8~12mm Mega-Pixel AVF Lens (External Control)

True Day & Night (ICR)

DC 12V


80 IR LED / Range up to 200ft



1080P LONG RANGE OUTDOOR IR BULLET CAMERA WITH ICR

2 MEGA PIXEL
Up To 1080p

X22 MORE COVERAGE than
Conventional CCTV Camera



HORIZONTAL RESOLUTION 1000 TV LINES

Sensor : 1/3" SONY CMOS / Min Illumination : 0 Lux at IR On (IR LED 80pcs)

DAY & NIGHT FUNCTION

This camera has a function that automatically selects the mode that is appropriate for daytime or night-time conditions. The COLOR mode operates in daytime conditions to provide optimum colors, and BW mode operates in nighttime conditions to enhance the definition of the image.

SINGLE SCAN WDR (WIDE DYNAMIC RANGE)

By adopting a proprietary 1/3" SONY CMOS chip, the camera delivers clear, high quality pictures even in backlight, by increasing exposure in dark areas while decreasing it in bright areas; a corrected image with clear details results.

PRIVACY FUNCTION

The PRIVACY function enables you to select and record only choose area among twenty-eight areas.

ADDITIONAL FUNCTION

White Balance, Motion Detection, Mirror, Sharpness, Freeze, Digital Zoom, Shading, HLM, ACE function are also available.

CONTROLLED OSD mENU

The camera can be controlled by selecting text displayed on the monitor screen.

XIR 2282FV	
Resolution	HD-SDI(1080p, 720p) / 1000 TV line over
Sensor	1/3" Sony CMOS
Total Pixels	2010(H) × 1108(V) = 2.2M Pixel
Effective Pixels	1944(H) × 1092(V) = 2.1M Pixel
Scanning System	Progressive
S/N (Y signal)	More than 52 dB (AGC Off)
Video Output	SMPT292M (HD-SDI)
Min.Illumination	0 lux at IR On
White Balance	Auto / Auto EXT / Pushing / Manual
Electronic Shutter Speed	Auto / Manual (1/30sec ~ 1/30,000sec)
Brightness	Adjustable (0 ~ 20 Step)
SENS_UP	Off / ×2 / ×3 / ×4
DNR	Off / Low / Middle / Hi
WDR / BLC	Off / WDR / BLC
HLM	Off / Set
ACE	Off / On
Day & Night	Auto (Day <-> Night time change) , Color , B/W
Privacy	Off / On (28 Zone)
Motion Detection	Off / On
D.ZOOM	0 ~ ×11.2
FLIP	Off / On
FREEZE	Off / On
Language	English
Sharpness	Adjustable (0 ~ 10 Step)
Mirror	On / Off
COMM.	RS-485(PELCO-D)
Operating Temperature / Humidity	14 °F~122 °F (-10 °C~+50 °C) / 30%~80% RH
Storage Temperature / Humidity	-4 °F~+140 °F (-20 °C~+60 °C) / 20%~90% RH
Power	DC 12V
Distance	300 ~ 450ft (100 ~ 150m)
Transmission Range	Max transmission range is depends on the cable manufacturer and the installation environment.

Specifications may change without a prior notice. All the images on the page are for illustrative purpose only. They may not representing actual products. All the rights for the registered trademarks are reserved for their respectable owners. Not responsible for any typographical errors.

sales@collsam.com

HTTPS://COLLSAM.COM

support@collsam.com

MADE IN KOREA

Images May Not Reflect the Actual Product.

(213) 210-6744

Design and specifications are subject to change without notice.