



- 1/2.9 inch SONY CMOS (IMX-326)
- IP 68 Ingress Protection
- 0 Lux at IR On (IR06)
- WDR (Wide Dynamic Range)
- DNR (Digital Noise Reduction)
- Day and Night
- ICR Varifocal lens
- DC Auto IRIS Varifocal Lens
- DC Auto IRIS and TDN Varifocal Lens
- Focal Length: 2.8~12mm

SPECIFICATIONS

Resolution	1440P, 1080P, 720P
Sensor	1/2.9 inch SONY CMOS (IMX-326)
Total Pixels	3096(H) × 2218(V) = 6.87M
Scanning System	PROGRESSIVE
S/N (Y signal)	More than 52 dB (AGC Off)
Video Output	TVI, CVBS: 1.0Vp-p (75ohm)
Min.Illumination	0 Lux at IR On
White Balance	AUTO / AUTO EXT / PRESET / MANUAL
Electronic shutter speed	AUTO / MANUAL (1/30sec ~ 1/30,000sec) / FLICKER
Brightness	ADJUSTABLE (0 ~ 20 STEP)
DNR	OFF / LOW / MIDDLE / HIGH
BACKLIGHT	OFF / WDR / BLC / HLC
Day & Night	AUTO (Day <--> Night TIME Change) , COLOR , B/W, EXTERN
PRIVACY / MOTION	OFF / ON
Language	ENG, CHN, CHN(S), JPN, KOR
Sharpness	ADJUSTABLE (0 ~ 10 STEP)
COMM.	RS-485(PELCO-D)
Temperature/Humidity	Operating 14 °F (-10 °C) ~ 122 °F (50 °C) / 30% ~ 80% RH) Storage -4 °F (-20 °C) ~ 140 °F (60 °C) / 20% ~ 90% RH)
Power	AC 24V / DC 12V Dual Power