



- 1/2.7" 4 Megapixel Sensor
- TVI 4MP 4-IN-1
- 8 ~ 12 mm Motorized 5 Megapixel Lens
- Indoor/Outdoor IR Vandal
- IR Cut Filter
- 4 white array LEDs, 30~35m IR distance
- Support UTC function
- OSD cable
- HDCVI/AHD/TVI/CVBS 4-IN-1 output
- 2D DNR

## SPECIFICATIONS

Image Sensor:	1/2.7" 4Mega Pixel Sensor
Effective Pixels:	4.0 Mega Pixels
Built-in Lens:	2.8 ~ 12mm Motorized 5Mega Pixel Lens
Signal System:	PAL/NTSC
Horizontal Resolution	PAL:2560 × 1440P 25F/S NTSC:2560 × 1440P 30F/S
Sync. System:	Internal Sync.
Sensor Area:	38mm × 38mm
Video Output:	TVI & CVI&AHD& CVBS Output
S/N Ratio:	More than 50dB (AGC OFF)
OSD Menu	Support
White Balance:	Auto Tracking White Balance
Shutter Speed:	1/25 ~ 50,000Sec.
Leds:	4 white array LEDs
Working Temperature:	14°F ~ 122°F(-10°C ~ 50°C)
Storage Temperature:	-4°F ~ 140°F(-20°C ~ 60°C)
Power Requirement:	DC12V, Max Power consumption Less Than 3W (When the infrared lamps turn on)
Weight:	1kg(2.2lb)