

**EX-SDI 4MP Outdoor IR Bullet Camera with Vari-Focal Lens, IP68, 6 COB IR, Dual Power**



1/2.9 inch SONY CMOS (IMX-326) • Upgraded Waterproof Housing (IP 68 rating) • High Definition Serial Digital Interface • 0 Lux at IR On (IR06) • WDR (Wide Dynamic Range) • DNR (Digital Noise Reduction) • Day & Night • ICR V/F lens, DC Auto IRIS V/F Lens, DC Auto IRIS & TDN V/F Lens • Focal Length : 2.8~12mm

**SPECIFICATIONS**

|                  |                                |
|------------------|--------------------------------|
| Resolution       | 1440P, 1080P, 720P             |
| Sensor           | 1/2.9 inch SONY CMOS (IMX-326) |
| Total Pixels     | 3096(H) × 2218(V) = 6.87M      |
| Scanning System  | PROGRESSIVE                    |
| S/N (Y signal)   | More than 52 dB (AGC Off)      |
| Video Output     | SMPTE274M (EX-SDI, HD-SDI)     |
| Min.Illumination | 0 Lux at IR On                 |

## EX-SDI 4MP Outdoor IR Bullet Camera with Vari-Focal Lens, IP68, 6 COB IR, Dual Power

|                          |                                                                                                                                      |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| White Balance            | AUTO / AUTO EXT / PRESET / MANUAL                                                                                                    |
| Electronic shutter speed | AUTO / MANUAL (1/30sec ~ 1/30,000sec) / FLICKER                                                                                      |
| Brightness               | ADJUSTABLE (0 ~ 20 STEP)                                                                                                             |
| DNR                      | OFF / LOW / MIDDLE / HIGH                                                                                                            |
| BACKLIGHT                | OFF / WDR / BLC / HLC                                                                                                                |
| Day & Night              | AUTO (Day <--> Night TIME Change) , COLOR , B/W, EXTERN                                                                              |
| PRIVACY / MOTION         | OFF / ON                                                                                                                             |
| Language                 | ENG, CHN, CHN(S), JPN, KOR                                                                                                           |
| Sharpness                | ADJUSTABLE (0 ~ 10 STEP)                                                                                                             |
| COMM.                    | RS-485(PELCO-D)                                                                                                                      |
| Temperature/Humidity     | Operating (14°F ~ 122°F(−10°C ~ 50°C)/ 30% ~ 80% RH) / Storage (−4°F ~ 140°F(−20°C ~ 60°C) / 20% ~ 90% RH)                           |
| Power                    | AC24V / DC12V Dual Power                                                                                                             |
| Signal Transmission      | The distant difference is occurred according to cable option and other circumstances. (based on 5C-HFBT : HD-SDI 100M / EX-SDI 500M) |