

# Eyemax MP4132V 4MP EX-SDI Outdoor Turret IR Camera, IP67, Motorized Varifocal Lens, 50ft (15m) IR Range, DC 12V



Eyemax UIU-MP4132V a powerful and reliable option for your video surveillance needs. Featuring advanced HD-SDI technology, this 4MP EX-SDI Vandal DOME Camera delivers full 1080p video without requiring costly upgrades. With a resolution of 1440P and 2704(H) × 2104(V), this camera captures every detail with exceptional clarity and precision.

Equipped with a 2.8-12mm dual power Varifocal lens, the UIU-MP4132V allows for flexible viewing options. Clear images in any lighting conditions are enabled by the DC auto IRIS and TDN ICR functionality of the lens. Whether it's day or night, this camera ensures that you have full visibility of your surroundings.

This camera features a 1/2.9" SONY CMOS (IMX-335) sensor and 1 Lux at F1.2. The True WDR (Wide Dynamic Range) feature ensures that high contrast scenes are captured accurately, eliminating overexposed or underexposed areas. The DNR technology also helps to keep image quality by reducing noise and producing clear, sharp footage.

# Eyemax MP4132V 4MP EX-SDI Outdoor Turret IR Camera, IP67, Motorized Varifocal Lens, 50ft (15m) IR Range, DC 12V

## SPECIFICATIONS

Resolution	1440P
Lens	Motorized Lens 2.8~12mm
Sensor	1/2.8 inch SONY® CMOS (IMX-335)
Pixels	Total : 2704(H) × 2104(V) = 5.69M / Effective : 2616(H) × 1964(V) = 5.14M
Scanning System	PROGRESSIVE
S/N (Y signal)	More than 52 dB (AGC Off)
Video Output	SMPTE274M EX-SDI (CVBS)
Frame Rate	4MP@30fps
Min.Illumination	0 Lux at IR On (IR LED 20)
White Balance	Auto / Auto Ext / Preset / Manual
Electronic shutter speed	AUTO / MANUAL (1/30sec ~ 1/30,000sec) / FLICKER
Function	DNR / ACE / WDR / BLC / HLC / Sens_up / Privacy / Flip / Motion / Defog / RS-485 / Sharpness / Smart IR / Brightness
Day & Night	AUTO (Day <--> Night TIME Change) , COLOR , B/W, EXTERN
Language	ENG, CHN, CHN(S), JPN, KOR
IR Distance	15M
Temperature/Humidity	Operating 14 °F (-10 °C) ~ 122 °F (50 °C) / 30% ~ 80% RH Storage -4 °F (-20 °C) ~ 140 °F (60 °C) / 20% ~ 90% RH
Power	DC 12V
Dimensions	Ø 4.09 inch (10.39 cm)e 3.54 inch (8.99 cm)
signal Transmission	The distant difference is occurred according to cable option and other circumstances.