

- 1/2.5" 5 Megapixel Sensor
- TVI up to 5MP@20fps, default output TVI 4M@30fps
- TVI/CVI/AHD/CVBS 4-IN-1
- 2.8~12 mmmegapixel motorized lens
- IR Cut Filter, 2DDNR
- 4 white power COB LEDs 115ft(35m) IR Distance
- Support UTC function
- toggle cable



## SPECIFICATIONS

Image Sensor	1/2.5" 5 Megapixel Sensor
Effective Pixels	5.0 Megapixel
Built-in Lens	2.8 ~ 12mm 5Megapixel Lens
Signal System	PAL/NTSC
Horizontal Resolution	NTSC: 2560 × 1440P (30F/S 4MP output/ 2560 × 1944 (20F/S 5MP output) PAL: 2560 × 1440P (25F/S 4MP output) / 2560 × 1944 (20F/S 5MP output)
Sync. System	Internal Sync.
Video Output	TVI & CVI & AHD & CVBS Output
S/N Ratio	More than 50dB (AGC OFF)
DNR	2D
OSD Menu	Support
UTC	Support by UTC
White Balance	Auto Tracking White Balance
Shutter Speed	1/25 ~ 50,000Sec.
Weather-proof	IP67
Protection Level	IP67
Working Temperature	14 °F (-10 °C) ~ 122 °F (50 °C)
Storage Temperature	-4 °F (-20 °C) ~ 140 °F (60 °C)
Power Requirement	DC12V, Max Power consumption Less Than 3W (When the infrared lamps turn on)
Weight	1.76 lbs (0.80kg)