



## Features

- 1/2.9 inch SONY CMOS (IMX-291)
- High Definition 2Megapixel (1080P)
- 0 Lux at IR On (IR LED 33 pcs)
- DNR (Digital Noise Reduction)
- WDR (Wide Dynamic Range) Day
- Easy Installation
- ICR Varifocal lens
- DC Auto IRIS Varifocal Lens
- TDN Varifocal Lens
- 5~50mm Focal Length

The Eyemax ULP-P2132VE-W camera can see car license plates from up to 300 feet (91.44 m) away. This camera makes it easy to get clear and precise images of license plates. Businesses, parking lots, and law enforcement agencies rely on it to keep an eye on vehicle movement.

Featuring a 1/2.9" Sony CMOS (IMX-291) sensor, this camera delivers high-resolution images with impressive detail and clarity. It's easy to identify vehicle information and track movements with the 1080P resolution. This camera has 33 LEDs that can capture plates in low or no light. This feature is especially useful for monitoring parking lots and garages at night.

The ULP-P2132VE-W camera is designed to make license plate capture hassle-free and efficient. The built-in 5-50mm varifocal lens eliminates the need for guesswork when choosing the right lens for the job. This feature is especially useful for locations with varying distances between the camera and the vehicle. Its Wide Dynamic Range (WDR) and Digital Noise Reduction (DNR) technologies ensure that the captured images are clear and free of any distortions, making it easier to read and recognize license plates.

## SPECIFICATIONS

Resolution	1080P, 720P,
Sensor	1/2.9 inch SONY CMOS (IMX-291)
Total Pixels	1945(H) x 1109(V) = 2.16M
Effective Pixels	1945(H) X 1097(V) = 2.13M
Scanning System	PROGRESSIVE
S/N (Y signal)	More than 52 dB (AGC Off)
Video Output	SMPTE292M (EX-SDI, HD-SDI) / (TVI, CVI, CVBS: 1.0Vp-p (75ohm) : Option)
Min.Illumination	0 Lux at IR On
White Balance	AUTO / AUTO EXT / PRESET / MANUAL
Electronic shutter speed	AUTO / MANUAL (1/30sec ~ 1/30,000sec) / FLICKER
SENS_UP	OFF / X2 ~ x32
DNR / ACE	OFF / LOW / MIDDLE / HIGH
BACKLIGHT	OFF / WDR / BLC / HLC
Dayand& Night	AUTO (Day <--> Night TIME Change) , COLOR , B/W, EXTERN
PRIVACY / FLIP / MOTION / DEFOG	OFF / ON
Language	ENG, CHN, CHN(S), JPN, KOR
Sharpness / Smart IR / Brightness	ADJUSTABLE (Sharpness : 0 ~ 10 STEP / Smart IR, Brightness : 0 ~ 20 STEP )
COMM.	RS-485(PELCO-D)
Temperature/Humidity	Operating 14 °F (-10 °C) ~ 122 °F (50 °C) / 30% ~ 80% RH Storage -4 °F (-20 °C) ~ 140 °F (60 °C) / 20% ~ 90% RH
Power	DC12V
signal Transmission	The distant difference is occurred according to cable option and other circumstances. (based on 5C-HFBT : HD-SDI (200M) / EX-SDI (500M))

WE SECURE YOUR LIFE

