



Day/Night 10pcs Super Flux IR LED • IK5 and IP66 Weatherproof Internal Micro SD • ICR Day/ Night with 3.6mm DC Iris Lens • Free Software for Mobile(Android/iPhone/iPad)

SPECIFICATIONS

Camera	
Sensor	Sony Exmor™ 1/2.8"
Max Resolution / FPS	1920 × 1080 / 30fps
Min Illumination	0.1Lux@F1.2(color) (0Lux IR LED On)
Day / Night	True Day / Night with ICR Filter
IR LEDs	10pc Super Flux IR LED 850mm for 20 ~ 25 Meters(65 ~ 82 feet)
Lens	3.6mm IR Corrected
Video Output	Service BNC output dangle cable with IP OSD from screw fit panel

IP Power / 2MP / Outdoor Bullet(IP66) / ICR / 3.6mm / 8+2 IR / BNC / Micro SD slot / DC 12V/PoE

Electronic Shutter	Auto / User 1/5 ~ 1/50, 0000, 60/60Hz software selectable
Parameters	
Compression	H-264 Hight Profile (Support Baseline Profile) / MJPEG
Bit Rate(CBR/VBR)	Stream1 50Kbps~12Mbps, Stream2 10Kbps~6Mbps, Stream3 (Fixed)
Quality Setting	1 ~ 9(9 highest)
Multi-Streaming	User setting of Stream 1/2 at supported Resolutions, Stream3 MJPEG Stream
Brightness / Sharpness	Variable 0 ~ 100 / 0 ~ 100
Gain Control	Auto / Fixed 8 ~ 102db
Orientation	Horizontal Mirror / Vertical Flip
Text Overlay	Time / Date / Camera / Custom OSD
Masking	5 User defined masking areas > 8% of total picutre
Network	
Etdernet	1 Etdernet(10/100 Base-T) RJ-45 Connector
TCP/IP	IPv4/IPv6 (DHCP / Fixed)
Compliance	Onvif v2.2 Profile-S Listed
RTSP Video	Standard RFC2326, Support QuickTime / VLC Player. User security autdentication(Enabled/Disabled)
Web Language	English
Recording Simultaneous	Local Micro SD Memory, Remote FTP server, TCP/UDP CMS, RTSP connection (stream 1,2 and 3)
Network Protocols	HTTP, TCP/IP, UDP/IP, RTSP, FTP, DHCP, NTP, Ppoe, NTP, Unicast and Multicast supported
Memory Card Slot	Internal memory card supports Max 64GB. Supports Edge Recording
Audio	
Input/Output	1 x RCA Input / 1 x RCA Output @ 1v Line Level
Audio Compression	G711 A-Law, G711 U-Law, RAW_PCM
GENERAL	
Power	12v DC@560mA (IR LED On) / PoE Class 3
Temperature	Operating: 14°F to 131°F (-10°C ~ 55°C) Storage: -4°F ~ 140°F(-20°C ~ 60°C)
Operating Humidity	10% ~ 85% RH
Approvals	CE/FCC/RoHS Compliant/IP66/IK5

IP Power / 2MP / Outdoor Bullet(IP66) / ICR / 3.6mm / 8+2 IR / BNC / Micro SD slot / DC 12V/PoE

Product Dimensions	265.5 × 69mm (10 2/5" × 2 3/4")
Product Weight	1.49lb/0.68kg