

Outdoor Infrared IP Bullet Camera / 2.1MP / Varifocal Lens / IR LED / PoE



2.1 MegaPixel Resolution • 2.8~12mm Vari-focal Lens • Mechanical IR-Cut Filter • DWDR (Digital Wide Dynamic Range) • Power over Ethernet (PoE) • ONVIF Compliant • 160 ft IR distance • H.264 • DC 12V

FEATURES

- 1/2.8in 2.1 Mega progressive scan CMOS
- H.264 H.265 1080p realtime recording

Outdoor Infrared IP Bullet Camera / 2.1MP / Varifocal Lens / IR LED / PoE

- Support intrusion detection
- 2D/3D DNR, DWDR, ROI, Anti-fog, IR_CUT
- Triple-Stream, Mobile APP, Support P2P
- Support PoE, Reset button, IR Array, TF Card
- Support ONVIF
- IP66

SPECIFICATIONS

Sensor	1/2.8" 2.1Mega progressive scan CMOS
Min.illumination	Colour:0.01Lux/F1.2; 0Lux/F1.2(IR ON)
Lens	2.8 ~ 12mm Vari-focusing lens
IR distance	Up to 160ft
Electronic shutter	Auto(1/25s-1/10000s Adjustable)
Day/Night	Auto/Color / B&W (IR_CUT)
Noise Reduction	2D/3D Digital Noise Reduction
Anti-fog	Support
WDR	Digital WDR
Image Adjustment	Sharpness,Brightness,Saturation,Contrast Adjustable
Video Encoding	H.264, h.265
Encoding Type	H.265:MainProfile; H.264:High Profile/Main Profile/BaseLine Profile
Record Resolution	Main Stream: 1920*1080@25fps/30fps; Sub Stream: 704*576@25fps; Third Stream:1280*720@25fps
Video Bitrate Control	Support VBR/CBR
Video Bitrate Range	32Kbps~8Mbps
Audio	1 Audio Input ; 1 Audio Output
Alarm	1 Alarm input ; 1 Alarm output
Storage	Support Micro SD/SDHC/SDXC Card Max 128G
RS485	Support
Reset Button	Built-in reset button
CVBS output	Support

Outdoor Infrared IP Bullet Camera / 2.1MP / Varifocal Lens / IR LED / PoE

Network Interface	RJ45 10M/100M adaptive Ethernet interface
Motion Detection	Multiple detection zones, variable sensitivity levels
ROI	Support
Corridor Mode	Support
Privacy Masking	Four zones for privacy masking
Snapshot	JPEG capture,capture resolution is the max coding resolution
Security Features	Support password protection, watermarking features
Text Overlay	Support (Channel name and time title)
Alarm	Support network anomaly,mask alarm and etc.
Intelligent Function	Support line-crossing detection
Mobile APP.	IOS, Andriod
Network Function	TCP/IP / UDP / HTTP / IGMP / ICMP / DHCP / RTP / RTSP / DNS / DDNS / FTP / NTP / PPPOE / UPNP / SMTP
Protocol	Support ONVIF and CGI protocol
Protection Grade	IP66
PoE	Support
Power	DC 12V
Operation Temperature	14°F ~ 140°F(-10°C ~ 60°C)
Operation humidity	10% ~ 90%
Power supply	10W MAX
Dimensions	98*96*265(mm)
Weight	1200g