



## V2000D-PTZ Roughneck Series Outdoor Network PTZ Dome Cameras



### Overview

Available in 2 MP or 5 MP, Vicon's Roughneck® V2000D-PTZ Series features advanced imaging and advanced analytics in a durable package. This powerful camera delivers exceptional views with a powerful 30x optical/8x digital zoom along with a motorized focus and auto IRIS lens. It's rated for IP66 and housing is IK10 rated (lens cover is IK07) to withstand any type of environment.

The V2000D-PTZ series is engineered to deliver clear images day or night. True WDR ensures the camera can overcome high-contrast lighting conditions during the day, while adaptive IR prevents overexposure and uneven views in darkness. Additionally, the camera includes Starlight low-light imaging to capture clear, color footage in extremely low light scenes. This helps operators see critical forensic details, such as vehicle or clothing color, when traditional cameras would show black-and-white IR images.

This PTZ camera offers both H.264 and H.265 compression and smart encoding technology to reduce bandwidth and storage without sacrificing quality. It also offers our advanced analytics package for proactive surveillance and automatic alerts. The camera meets the latest regulations required to be NDAA approved. Several mounting options are available; refer to Ordering Information.

### Product at a Glance

- ▶ 2 MP and 5 MP resolution models
- ▶ Starlight low-light imaging
- ▶ H.265/H.264
- ▶ Advanced analytics
- ▶ True WDR (120 dB); built-in varifocal autoiris lens
- ▶ 30X optical zoom; 8X digital zoom
- ▶ PoE++; 24 VAC; 48 VDC
- ▶ Triple streaming video
- ▶ Two-way audio; two alarm inputs/alarm outputs
- ▶ Heater/blower system for temperature control
- ▶ IP66 and IK10 (housing) rated
- ▶ Supports local recording to SDHC/SDXC card
- ▶ ONVIF (Profile S/G/Q/T) interface provides inter-operability with open platform solutions
- ▶ NDAA/GSA/TAA compliant

## Specifications

Model	V2002D-PTZ
Image Sensor:	1/2.8 inch Sony
Max Resolution:	2 MP (1080p)
Image Settings:	Digital image effects: defog, flip and mirror. Configurable brightness, contrast, saturation, hue, sharpness. White balance. Backlight Compensation (BLC). HLC. Gain control. Gamma correction. Electronic shutter speed. Day/night mode. Dynamic Noise Reduction (3 DNR). Motion detection (4 programmable zones). Privacy masking (8 masks). Dynamic ROI. Event notification. Electronic Image Stabilization (EIS).
Intelligent Video Analytics:	5 profile/presets: Motion, Tampering/Defocus, Intrusion, Loitering, Line Cross/Counting, Object Left/Removed, Area Counting, Wrong Direction. Museum Search.
Electronic Shutter Speed:	1/30 ~ 1/10,000 sec
Day/Night Performance:	True day/night (IR cut filter)
Wide Dynamic Range (WDR):	True WDR (120 dB)
Minimum Illumination:	Color: 0.007 lux; B/W: 0.002 lux
IR Distance:	Adaptive IR; Smart IR (Automatic): 492 ft (150 m)
<b>Lenses</b>	
Focal Length:	4.5 - 135 mm (30X optical zoom); digital 8X
Max. Aperture:	f/1.6 - f/4.4
Iris:	Autoiris
Zoom/Focus Adjust:	Motorized focus and zoom
Field of View:	5° - 60° (H); 3° - 38° (V)
<b>Network Video Transmission</b>	
Network:	10Base-T, 100Base-TX, RJ-45
Image Compression:	H.265/H.264 and M-JPEG
Resolution:	1920×1080 (1080P), 1280×960/720, 800×600, 640×480, 640×360, 320×240
Protocol:	ARP, DHCP, DNS, FTP, HTTP, HTTPS, HLS, ICMP, IGMP, IPv4/6, LDAP, NTP, RTSP/RTCP/RTP, RTMP, QoS, SMTP, SNMP v1/2c/3, TCP, TLS/TLS, UDP, UPnP, 802.1X, UPnP, Bonjour, DDNS, PPPoE; ONVIF S/G/Q/T
Frame Rate:	Max. 30 fps (25 fps, PAL)
Streams:	Triple streaming. Single: 2 MP@30fps; Dual: 2 MP@30fps + 720p@15fps; Triple: 2 MP@30fps + 720@15fps +VGA @30fps
Users:	Live viewing for up to 10 clients
Web Browser:	Internet Explorer®, Safari®, Firefox®, Google Chrome®, Microsoft® Edge
Security:	IP address filtering, HTTPS encrypted data transmission, SSL, IEEE 802.1X, Digest Authentication, Advanced Security
Local Recording:	Micro-SD slot provided; customer supplied SDHC/SDXC card
<b>Mechanical</b>	
Construction:	Aluminum base; polycarbonate dome bubble
Pan Range:	360° continuous pan
Pan Speed:	300°/second maximum
Tilt Range:	95° (-15° to 90°)
Tilt Speed:	160°/second maximum
Presets:	128
Tours/Pattern:	4/4
Alarm:	2 alarm inputs; 2 alarm output
Audio Capability:	Two-way audio; G.711 compression
Mounting:	Mounting accessories available. Refer to Ordering Information
Dimensions:	7.5 in. (190 mm) (Diam) x 13.2 in. (336 mm) (H); refer to dimensional diagram
Weight:	11.5 lb (5.2 kg)

## Specifications

<b>Model</b>	V2000D-PTZ
<b>Electrical</b>	
Input Power:	PoE++ (IEEE 802.3bt, Class 7); 24 VAC (+20%/-10%); 48 VDC (±10%)
Current (IR on):	2.5 A @24 VAC; 1.25 A @48 VDC
Power Consumption:	Total Power: 48 W. PTZ Camera: 11 W; Pan/Tilt Function: 12 W; IR: 19 W; Heater: 5.5 W; Blower: 0.9 W. Note that blower is always on; heater turns on when temperature is lower than 59° F (15° C)
<b>Controls and Connectors</b>	
Indicators and Connectors:	Power: 24 VAC/48 VDC: terminal block. Network/PoE: RJ-45 CAT 5. Audio In/Out and Alarm In/Out: screw terminal. SDHC/SDXC Card Slot. Reset button. Default button. Indicators: green LED flashes for booting and software updating
<b>Environmental</b>	
Operating Conditions:	Temp: -40° to 140° F (-40° to 60° C) Humidity: up to 90%, relative, non-condensing Limitations in certain weather conditions, including blizzard conditions and freezing rain with high winds.
Approvals:	UL; FCC Class A; CE; IP66; IK10 (housing)/IK07 (lens cover); RoHS
Country of Origin:	Taiwan
Warranty:	5 years

## Dimensional Drawing [mm (in.)]

