



## FEATURES

- 8MP ( 3840 × 2160 ) H.265 coding
- Max.resolution: 3840 × 2160
- ICR auto switch, true day / night, ROI coding
- 3D DNR, WDR, HLC, BLC, defog
- 20~30m IR night view distance
- DC12V/PoE power supply
- P2P function optional
- IP 67 ingress protection
- Support three streams
- Support mobile surveillance by smart phones with iOS or Android OS
- Intelligent analytics:Region intrusion detection, scene change detection and line crossing detection

# IP Power C8232 | 8MP (4K) Network IP67 Outdoor IR Turret Camera, H.265, Fixed Lens, up to 100ft, DC 12V / PoE

## SPECIFICATIONS

Camera	
Image Sensor	1 / 2.7"CMOS
Image Size	3840 × 2160
Electronic Shutter	1 / 25 s ~ 1 / 100000 s
Iris Type	Fixed Iris
Min. Illumination	0.11 lux @F2.2, AGC ON; 0 lux with IR 0.032 lux @ F1.2, AGC ON; 0 lux with IR
Lens	2.8 mm @F2.0, (fixed lens), horizontal field of view: 112° 3.6 mm @F2.2, (fixed lens),horizontal field of view: 89°
Lens Mount	M12
Wide Dynamic Range	Digital WDR
BLC	Yes
HLC	Yes
Defog	Yes
Digital NR	3D DNR
Angle Adjustment	Pan: 0° ~ 360°; Tilt:0° ~ 75°; Rotation: 0° ~ 360°
Image	
Video Compression	H.265 / H.264
H.264 Compression Standard	Baseline Profile/Main Profile/High Profile
Resolution	8MP ( 3840 × 2160 ), 6MP ( 3072 × 2048 ), 5MP ( 2592 × 1944 ),720P ( 1280 × 720 ), D1, CIF, 480 × 240
Main Stream	8MP/ 6MP/ 5MP(1 ~ 20fps)
Sub Stream	720P/D1/CIF (1 ~ 20fps)
Third Stream	D1/CIF/480 × 240(1 ~ 20fps)
Bit Rate	64 Kbps ~ 8 Mbps
Bit Rate Type	VBR / CBR
Audio Compression	G711A / U
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR,etc. adjustable through client software or web browser

# IP Power C8232 | 8MP (4K) Network IP67 Outdoor IR Turret Camera, H.265, Fixed Lens, up to 100ft, DC 12V / PoE

ROI	Each ROI to be configured separately
<b>Interfaces</b>	
Network	RJ45
Video Output	No
Audio	1CH built-in MIC; 1CH audio input
Storage	Built-in micro SD card slot; up to 128GB
Hardware Reset	Yes
<b>Functions</b>	
Remote Monitoring	Web browsing, CMS remote control
Online Connection	Support simultaneous monitoring for up to 3 users; Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, 802.1x, UPnP, HTTP, HTTPS, QoS
Interface Protocol	ONVIF
Storage	Network remote storage; micro SD card storage
Smart Alarm	Motion detection, SD card error, SD card full
Intelligent Analytics	Region intrusion detection, scene change detection and line crossing detection
General Function	Watermark, IP address filtering, video mask, heartbeat, illegal login lock
PoE	Yes
IR Distance	20 ~ 30 m
Ingress Protection	IP 67
<b>Others</b>	
Power Supply	DC12V/PoE
Power Consumption	< 6W
Operating Environment	-30°C ~ 60°C (-22°F ~ 140°F); Humidity: less than 95 % (non-condensing)
Dimensions ( mm )	Φ 94.6 × 82.8
Weight ( net )	Approx. 0.47KG
Installation	Ceiling mounting ( Wall mounting available with the junction box and bracket )

**Distributed By**

Collsam Distributions, Inc.  
 Sales: (951) 282-8707 sales@Collsam.com  
 Support: (213) 210-5744 support@Collsam.com  
 Website: www.Collsam.com

