

Features

- 1/2.9" SONY CMOS sensor.
- Extended Serial Digital Interface
- 1 LUX @F1.2, 0.1 LUX Black and white
- DNR (Digital Noise Reduction)
- Day and Night (ICR Option)
- Easy Installation



SPECIFICATIONS

Resolution	1080P 2 Megapixel
Sensor	1/2.9" SONY CMOS (IMX-222 / IM × 322)
Total Pixels	2000(H) × 1241(V) = 2,482,000
Effective Pixels	1944(H) × 1092(V) = 2,122,648
Scanning System	PROGRESSIVE
S/N (Y signal)	More than 52 dB (AGC Off)
Video Output	SMPTE292M (HD-SDI) / (CVBS: 1.0Vp-p (75ohm) : Option)
Min.Illumination	1 LUX @F1.2 / 0.1 LUX Black and White
White Balance	AUTO
Electronic shutter speed	AUTO
DNR	ON
Day & Night	AUTO (Day <--> Night TIME Change)
Temperature/Humidity	Operating at 14 °F (-10 °C) ~ 158 °F (70 °C) / 30% ~ 80% RH) Storage at 14 °F (-10 °C) ~ 104 °F (40 °C) / 20% ~ 90% RH)
Power	12V DV
signal Transmission	The distant difference occurred according to cable option and other circumstances. (based on 5C-HFBT: HD-SDI 656.18 ft (200 m) / EX-SDI 1312.34 ft (400 m))