



- 1/2.9" SONY CMOS (IMX-222)
- HD-SD1/2.9" SONY CMOS (IMX-222)
- HD-SDI (1080P)
- EX-SDI (1080P) Extended Serial Digital Interface
- Day night (ICR Option)
- DNR (Digital Noise Reduction)
- Easy Installation
- Fixed Lens 3.7 mm
- Pinhole Lens 4.3 mm (1080P)

SPECIFICATIONS

Resolution	1080P
Sensor	1/2.9" SONY CMOS (IMX-222/IMX322)
Total Pixels	2000(H) x 1241(V) = 2482000
Effective Pixels	1999(H) x 1092(V) = 2122648
Scanning System	Progressive
S/N (Y Signal)	More than 52dB(AGC Off)
Video Output	SMPTE292M(HD-SDI)/(CVBS: 1.0Vp-p(75ohm) Option)
Min Illumination	1Lux at F1.2/0.1 Lux(B/W)
White Balance	Auto
Shutter	Auto(1/30sec - 1/60000sec
AGC	On
DNR	On
Day & Night	On
Operating Temperature / Humidity	14°F ~ 120°F(-10°C ~ 50°C) / 30% ~ 80% RH
Storage Temperature / Humidity	-4°F ~ 140°F(-20°C ~ 60°C) / 20% ~ 90% RH
Power	DC12V
Signal	The distant difference occurred according cable option and other circumstances. Based on 5C-HFBT HD-SDI(200M) / EX-SDI(400M)